

Prima Creator

PrimaValue PLA High Speed Gray

Material Engineering Report
MaterialID MAT0101

3DPiceland Engineering Platform
3DPiceland Labs
Generated with 3DPiceland Engineering Platform v60.0.6
WORKFLOW-RELIABILITY - Bug Fixes and Workflow Reliability
Generated 2026-08-25 19:02:26

Public-data contract: This static report contains only allowlisted material identity, public links, canonical MSRP and existing Verified Material Summary / governed score outputs. It excludes raw specimen rows and non-public operational data.

TEST COVERAGE

Complete

ENGINEERING AXES

6/6

PUBLIC MSRP

\$19.04 USD/kg

Material identity

MaterialID	MAT0101
Material	Prima Creator PrimaValue PLA High Speed Gray
Manufacturer	Prima Creator
Product line	PrimaValue
Base material	PLA
Category	Standard
Variant / finish	High Speed
Reinforcement	—
Color	Gray

Governed engineering profile


Overall	55/100
---------	--------

Tensile	30/100
Impact	61/100
Stiffness	76/100
Consistency	84/100
Layer adhesion	23/100
Thermal	27/100
Best available axis	consistency

Engineering score profile



Engineering radar



Fixture thermal result

53 °C · score 27/100 · method 3dp-thermal-deflection-fixture-v1

Nearby BlueDOT probe-indicated fixture temperature from a non-standard comparative 3DPIceland method; not ASTM D648, ISO 75, specimen temperature, certified HDT or a manufacturer limit.

Material and manufacturer context

Metric	Selected material	Material average	Manufacturer average
Overall	55/100	50/100	47/100
Tensile	30/100	29/100	27/100
Impact	61/100	24/100	33/100
Stiffness	76/100	87/100	76/100
Consistency	84/100	79/100	78/100
Layer adhesion	23/100	30/100	22/100
Thermal	27/100	—	—

Verified measurement results

Existing Verified Material Summary outputs. The public renderer does not read raw specimen rows or recalculate these values.

Measurement	Average	Std. deviation	CV	Samples	Confidence
Tensile upright	8.959 MPa	3.324 MPa	37.1%	8	8/10
Tensile flat	39.452 MPa	3.292 MPa	8.3%	10	10/10
Impact upright	261.776 kJ/m ²	30.534 kJ/m ²	11.7%	10	10/10
Impact flat	967.106 kJ/m ²	34.274 kJ/m ²	3.5%	10	10/10
Stiffness modulus	2277.929 MPa	—	—	—	—
Stiffness deflection	2.382 mm	—	—	—	—

Measurement provenance

Canonical per-module measured dates from SQLite, shown in unambiguous ISO format. Missing dates are not inferred.

Module	Measured date
Tensile	Not recorded
Impact	Not recorded
Stiffness	Not recorded
Thermal	Not recorded

Engineering interpretation

Summary: Prima Creator PrimaValue PLA High Speed Gray has a specialized or limited engineering profile. It is above its material-family average by 4,8 points and above its manufacturer average by 7,6 points. Its strongest measured axis is Consistency, while the weakest axis is Layer Adhesion.

Data-driven review: Prima Creator PrimaValue PLA High Speed Gray is best understood as a repeatable material for cosmetic, concept and low-load prototype work. Compared with the current verified dataset, it ranks better than 86% overall, is above the material-family average by 4,8 points, and is above the manufacturer average by 7,6 points. Its strongest engineering signal is Consistency, while Layer Adhesion is the main limitation to consider before using it for demanding applications.

BEST FEATURE

Consistency

MAIN LIMITATION

Layer Adhesion

DATASET POSITION

Better than 86%
33 / 234

Strengths

- Consistency: 84/100. Repeatability is one of the stronger signals in this material profile.
- Impact: 61/100. Impact behavior is competitive against the material-family context.
- Stiffness: 76/100. Stiffness is a relative advantage in this comparison group.

Limitations

- Tensile: 30/100. Avoid using this as the primary choice for tensile-loaded parts.
- Stiffness: 76/100. Expect less shape stability than the stronger materials in the same family.
- Layer adhesion: 23/100. Z-axis performance should be treated with caution.

Engineering trade-offs

- Good repeatability does not compensate for low tensile capability in load-bearing designs.

Recommended applications

- Rigid brackets, fixtures and shape-stable prototypes
- Impact-aware parts where toughness matters
- Repeatable print jobs and production-style batches
- Cosmetic parts, concept models or low-load prototypes
- Avoid high tensile load applications

Metric rankings and percentiles

Metric	Score	Rank	Percentile
Overall	55/100	33 / 234	Better than 86%
Tensile	30/100	100 / 226	Better than 56%
Impact	61/100	5 / 226	Better than 98%
Stiffness	76/100	123 / 223	Better than 45%
Consistency	84/100	31 / 231	Better than 87%
Layer adhesion	23/100	119 / 226	Better than 48%
Thermal	27/100	131 / 209	Better than 38%

Decision guidance

- Use this material for moderate requirements after checking the weakest axis.
- Review the listed alternatives if the application needs stronger overall performance.
- Do not choose it as a tensile-strength benchmark material.

Better alternatives

MaterialID	Material	Manufacturer	Overall	Tensile	Impact
MAT0069	ProtoPasta HTPLA Blood of My Enemies PLA Red	ProtoPasta	100/100	—	—
MAT0079	Polymaker PolyLight PLA Pro Black	Polymaker	65/100	35/100	52/100
MAT0109	Polymaker PolyMax PLA Black	Polymaker	64/100	32/100	62/100

Peer context

Highest-scoring same-base-material peers from the current governed dataset. This context is descriptive and is not recalculated by the public renderer.

MaterialID	Material	Manufacturer	Overall	Tensile	Impact
MAT0069	ProtoPasta HTPLA Blood of My Enemies PLA Red	ProtoPasta	100/100	—	—

MaterialID	Material	Manufacturer	Overall	Tensile	Impact
MAT0079	Polymaker PolyLight PLA Pro Black	Polymaker	65/100	35/100	52/100
MAT0109	Polymaker PolyMax PLA Black	Polymaker	64/100	32/100	62/100
MAT0080	Polymaker PolySonic PLA Pro Blue	Polymaker	64/100	30/100	58/100
MAT0076	BambuLab Tough+ PLA Tough+ Black	BambuLab	63/100	26/100	59/100
MAT0108	Polymaker PolyLight PLA Black	Polymaker	61/100	33/100	14/100
MAT0074	Winkle Matte PLA Matte Red	Winkle	60/100	34/100	—
MAT0122	Add:North Enhanced PLA Clear	Add:North	59/100	40/100	10/100

Public links

[Manufacturer website](#) [Download PDF](#)

Methodology and limitations

Results are comparative 3DPlceland measurements from home-built test equipment. Thermal is a nearby BlueDOT probe-indicated fixture temperature, not ASTM D648, ISO 75 or specimen temperature. Missing evidence remains n/a. Scores and test results are not recalculated by this publishing layer and do not replace certified manufacturer datasheets or accredited laboratory testing.

- [Testing methodology](#).
- [Engineering methodology whitepaper](#)