

Elegoo Standard Sea Green PLA Plus Green

Material Engineering Report
MaterialID MAT0193

3DPiceland Engineering Platform
3DPiceland Labs
Generated with 3DPiceland Engineering Platform v60.0.6
WORKFLOW-RELIABILITY - Bug Fixes and Workflow Reliability
Generated 2026-08-25 19:02:26

Public-data contract: This static report contains only allowlisted material identity, public links, canonical MSRP and existing Verified Material Summary / governed score outputs. It excludes raw specimen rows and non-public operational data.

TEST COVERAGE

Complete

ENGINEERING AXES

6/6

PUBLIC MSRP

\$11.86 USD/kg

Material identity


MaterialID	MAT0193
Material	Elegoo Standard Sea Green PLA Plus Green
Manufacturer	Elegoo
Product line	Standard
Base material	PLA
Category	Standard
Variant / finish	Plus
Reinforcement	—
Color	Green

Governed engineering profile


Overall	50/100
Tensile	31/100

Impact	29/100
Stiffness	85/100
Consistency	78/100
Layer adhesion	25/100
Thermal	25/100
Best available axis	stiffness

Engineering score profile



Engineering radar



Fixture thermal result

50 °C · score 25/100 · method 3dp-thermal-deflection-fixture-v1

Nearby BlueDOT probe-indicated fixture temperature from a non-standard comparative 3DPIceland method; not ASTM D648, ISO 75, specimen temperature, certified HDT or a manufacturer limit.

Material and manufacturer context

Metric	Selected material	Material average	Manufacturer average
Overall	50/100	50/100	50/100
Tensile	31/100	29/100	32/100
Impact	29/100	24/100	29/100
Stiffness	85/100	87/100	82/100
Consistency	78/100	79/100	80/100
Layer adhesion	25/100	30/100	25/100
Thermal	25/100	—	—

Verified measurement results

Existing Verified Material Summary outputs. The public renderer does not read raw specimen rows or recalculate these values.

Measurement	Average	Std. deviation	CV	Samples	Confidence
Tensile upright	10.167 MPa	3.633 MPa	35.7%	10	10/10
Tensile flat	39.959 MPa	2.835 MPa	7.1%	10	10/10
Impact upright	144.258 kJ/m ²	27.394 kJ/m ²	19%	10	10/10
Impact flat	438.254 kJ/m ²	123.105 kJ/m ²	28.1%	10	10/10
Stiffness modulus	2544.996 MPa	—	—	—	—
Stiffness deflection	2.132 mm	—	—	—	—

Measurement provenance

Canonical per-module measured dates from SQLite, shown in unambiguous ISO format. Missing dates are not inferred.

Module	Measured date
Tensile	Not recorded
Impact	Not recorded
Stiffness	Not recorded
Thermal	Not recorded

Engineering interpretation

Summary: Elegoo Standard Sea Green PLA Plus Green has a specialized or limited engineering profile. It is below its material-family average by 0,4 points and above its manufacturer average by 0,1 points. Its strongest measured axis is Stiffness, while the weakest axis is Layer Adhesion.

Data-driven review: Elegoo Standard Sea Green PLA Plus Green is best understood as a repeatable material for cosmetic, concept and low-load prototype work. Compared with the current verified dataset, it ranks better than 63% overall, is roughly aligned with the material-family average, and is roughly aligned with the manufacturer average. Its strongest engineering signal is Stiffness, while Layer Adhesion is the main limitation to consider before using it for demanding applications.

BEST FEATURE

Stiffness

MAIN LIMITATION

Layer Adhesion

DATASET POSITION

Better than 63%
87 / 234

Strengths

- Consistency: 78/100. Repeatability is one of the stronger signals in this material profile.
- Impact: 29/100. Impact behavior is competitive against the material-family context.
- Stiffness: 85/100. Stiffness is a relative advantage in this comparison group.

Limitations

- Tensile: 31/100. Avoid using this as the primary choice for tensile-loaded parts.
- Impact: 29/100. Avoid high impact or shock-loaded components without additional validation.
- Layer adhesion: 25/100. Z-axis performance should be treated with caution.

Engineering trade-offs

- Good repeatability does not compensate for low tensile capability in load-bearing designs.
- Stiffness is useful for shape stability, but impact tolerance is a separate limitation.
- The report should be read as a suitability warning rather than a general-purpose recommendation.

Recommended applications

- Rigid brackets, fixtures and shape-stable prototypes
- Repeatable print jobs and production-style batches
- Cosmetic parts, concept models or low-load prototypes
- Avoid high tensile load applications
- Avoid high impact components

Metric rankings and percentiles

Metric	Score	Rank	Percentile
Overall	50/100	87 / 234	Better than 63%
Tensile	31/100	85 / 226	Better than 63%
Impact	29/100	68 / 226	Better than 70%
Stiffness	85/100	97 / 223	Better than 57%
Consistency	78/100	122 / 231	Better than 48%
Layer adhesion	25/100	102 / 226	Better than 55%
Thermal	25/100	190 / 209	Better than 10%

Decision guidance

- Use this material mainly for low-load, visual or experimental parts.
- Review the listed alternatives if the application needs stronger overall performance.
- Do not choose it as a tensile-strength benchmark material.
- Avoid selecting it for impact-focused testing or shock-loaded designs.

Better alternatives

MaterialID	Material	Manufacturer	Overall	Tensile	Impact
MAT0069	ProtoPasta HTPLA Blood of My Enemies PLA Red	ProtoPasta	100/100	—	—
MAT0079	Polymaker PolyLight PLA Pro Black	Polymaker	65/100	35/100	52/100
MAT0109	Polymaker PolyMax PLA Black	Polymaker	64/100	32/100	62/100

Peer context

Highest-scoring same-base-material peers from the current governed dataset. This context is descriptive and is not recalculated by the public renderer.

MaterialID	Material	Manufacturer	Overall	Tensile	Impact
MAT0069	ProtoPasta HTPLA Blood of My Enemies PLA Red	ProtoPasta	100/100	—	—

MaterialID	Material	Manufacturer	Overall	Tensile	Impact
MAT0079	Polymaker PolyLight PLA Pro Black	Polymaker	65/100	35/100	52/100
MAT0109	Polymaker PolyMax PLA Black	Polymaker	64/100	32/100	62/100
MAT0080	Polymaker PolySonic PLA Pro Blue	Polymaker	64/100	30/100	58/100
MAT0076	BambuLab Tough+ PLA Tough+ Black	BambuLab	63/100	26/100	59/100
MAT0108	Polymaker PolyLight PLA Black	Polymaker	61/100	33/100	14/100
MAT0074	Winkle Matte PLA Matte Red	Winkle	60/100	34/100	—
MAT0122	Add:North Enhanced PLA Clear	Add:North	59/100	40/100	10/100

Public links

[Manufacturer website](#) [Download PDF](#)

Methodology and limitations

Results are comparative 3DPlceland measurements from home-built test equipment. Thermal is a nearby BlueDOT probe-indicated fixture temperature, not ASTM D648, ISO 75 or specimen temperature. Missing evidence remains n/a. Scores and test results are not recalculated by this publishing layer and do not replace certified manufacturer datasheets or accredited laboratory testing.

- [Testing methodology](#).
- [Engineering methodology whitepaper](#)