

Winkle Standard PETG Gray

MaterialID MAT0054



3DPiceland Labs
Generated with 3DPiceland Engineering Platform v60.0.6
WORKFLOW-RELIABILITY - Bug Fixes and Workflow
Reliability
2026-08-25 19:04:35

Traceability boundary: canonical per-module measured dates are shown below. Session identifier, time of day, operator, printer/slicer profile and environmental conditions are Not recorded and are never inferred.

Measurement provenance

Canonical SQLite measured dates use ISO format; missing dates remain Not recorded.

Module	Measured date
Tensile	Not recorded
Impact	Not recorded
Stiffness	Not recorded

Status Partial	Result modules 1/3	Specimen/result records 20	Public details Approved
--------------------------	------------------------------	---	-----------------------------------

Specimen and result quality

Module	Orientation	Average	Std. dev.	CV	Specimens	Confidence	Validation
Tensile	Upright	n/a	n/a	n/a	0	n/a	OK
Tensile	Flat	n/a	n/a	n/a	0	n/a	OK
Impact	Upright	53,889 kJ/m ²	14,879 kJ/m ²	0,276%	10	10/10	OK

Module	Orientation	Average	Std. dev.	CV	Specimens	Confidence	Validation
Impact	Flat	66,953 kJ/m ²	18,66 kJ/m ²	0,279%	10	10/10	OK
Stiffness	Three-point bend	n/a	n/a	n/a	0		OK

Recorded native inputs

Module	Input set	Recorded values
Tensile	Upright force inputs (N)	, , , , , , , ,
Tensile	Flat force inputs (N)	, , , , , , , ,
Impact	Upright needle inputs (%)	3,25, 2,50, 2,50, 3,50, 4,00, 4,50, 3,00, 4,00, 1,50, 3,50
Impact	Flat needle inputs (%)	3,00, 3,00, 3,50, 2,50, 4,50, 5,00, 6,00, 5,00, 4,00, 3,50
Stiffness	Revolutions / degrees	

Approved test notes

Method and equipment context

Purpose-built tensile, pendulum impact and three-point bend apparatus are used with the governed Settings Manager constants consumed by ResultsService. Results are comparative and do not claim accredited-laboratory equipment.

[Testing methodology](#) · [Engineering methodology whitepaper](#) · [Download PDF](#)

reports/test-sessions/MAT0054/